

Willamette Meridian through T. 26 S., between R's L W & 1 E.

16.65	CHAINS Bluff 30 ft. high.
18.70	Bluff, 20 ft. high.
33.00	Creek, 1 lk. wide, course W. Difference between measurements of 40.00 chs. by two sets of chainmen is 22 lks., position of middle point By 1st set, 39.89 chs. By 2nd set, 40.11 chs., the mean of which is
40.00	Point for $\frac{1}{4}$ sec. cor. on face of bluff.
42.55	A basalt rock in place, 3 x 2 x 2 ft., above ground, for witness cor. to the $\frac{1}{4}$ sec. cor., I mark with a cross (x) at exact cor. point, WC $\frac{1}{4}$ W, of cross, from which A fir, 12 ins. diam., bears S.43 $\frac{1}{2}$ *E., 131 lks. dist., marked W C $\frac{1}{4}$ S 18 B T. A white oak, 8 ins. diam., bears N.26 $\frac{1}{2}$ *W., 89 lks. dist., marked W C $\frac{1}{4}$ S 13 B T.
54.50	Ridge bears E and W. Descend NW slope.
70.00	Ravine, course W. Ascend SW slope. Difference between measurements of 80.00 chs. by two sets of chainmen is 40 lks., position of middle point By 1st set, 79.80 chs. By 2nd set, 80.20 chs., the mean of which is
80.00	Set a slate stone 16 x 6 x 4 ins., 11 ins. in the ground for cor. of secs. 7, 12, 13 and 18 marked with 2 notches on N and 4 notches on S edge, from which A fir, 12 ins. diam., bears N.39 $\frac{1}{2}$ *E., 74 lks. dist., marked T 26 S R 1 E S 7 B T. A fir, 6 ins. diam., bears S.68*E., 28 lks. dist., marked T 26 S R 1 E S 18 B T. A fir, 12 ins. diam., bears S.80*W., 84 lks. dist., marked T 26 S R 1 W S 13 B T. A fir, 12 ins. diam., bears N.8*W., 40 lks. dist., marked T 26 S R 1 W S 12 B T.