

County Surveyor's Record, Douglas County, Oregon

Willamette Meridian through T. 26 S., between R's 1 E and 1 W.

CHAINS	<p>A fir, 24 ins. diam., bears S.54*E., 53 lks. dist., marked T 26 S R 1 E S 7 B T.</p> <p>A cedar, 24 ins. diam., bears S.88*W., 59 lks. dist., marked T 26 S R 1 W S 12 B T.</p> <p>A hemlock, 24 ins. diam., bears N.30*W., 74 lks. dist., marked T 26 S R 1 W S 1 B T.</p> <p>Land mountainous.</p> <p>Soil stony, 4th rate.</p> <p>Timber fir, hemlock; undergrowth vine maple, arrowwood.</p> <p style="text-align: right;">July 22, 1910.</p>
0.75	<p>At the cor. of secs. 1, 6, 7 and 12.</p> <p>Thence I run,</p> <p>North between secs. 1 and 8.</p> <p>Over mountainous land, heavily timbered and covered with dense undergrowth.</p> <p>Descend N slope.</p> <p>Creek, 1 lk. wide, course N.20*E.</p> <p>Descend NE slope.</p>
18.85	<p>Creek, 8 lks. wide, course NW.</p> <p>Ascend SW slope.</p> <p>Difference between measurements of 40.00 chs. by two sets of chainmen is 12 lks., position of middle point</p> <p style="padding-left: 40px;">By 1st set, 39.94 chs.</p> <p style="padding-left: 40px;">By 2nd set, 40.06 chs., the mean of which is</p>
40.00	<p>Set a basalt stone 12 x 10 x 6 ins., 8 ins. in the ground for <math>\frac{1}{4}</math> sec. cor., marked <math>\frac{1}{4}</math> on W face, from which</p> <p>A cedar, 24 ins. diam., bears S.66*E., 67 lks. dist., marked <math>\frac{1}{4}</math> S 6 B T.</p> <p>A cedar, 20 ins. diam., bears N.58*W., 83 lks. dist., marked <math>\frac{1}{4}</math> S 1 B T.</p>
42.50	<p>Ridge bears E and W.</p> <p>Descend N slope.</p>