

Retracement of North Boundary of T. 26 S., R. 1 W., W. M.

CHAINS

A point of rock, 3 ft. high bears N.45\*E., 19 lks. dist., marked B O 36.

A maple, 6 ins. diam., bears N.76 $\frac{1}{2}$ \*W., 73 lks. dist., marked T 25 S R 1 W S 35 B T.

I obliterate marks on former bearing trees referring to T. 26 S.

Thence I run,

West on S boundary of sec. 35, T. 25 S., R. 1 W.

Over mountainous land, heavily timbered and covered with dense undergrowth.

Along S slope.

23.00 Creek, 1 lk. wide, course S.

Ascend E slope.

40.10 The  $\frac{1}{4}$  sec. cor., which is a post almost destroyed by fire, marked and witnessed as described by the Surveyor General.

I re-establish the cor. in its original position as the  $\frac{1}{4}$  sec. cor. on S boundary of sec. 35, T. 25 S., R. 1 W, only as follows:

Set a basalt stone 15 x 10 x 10 ins., 10 ins. in the ground for  $\frac{1}{4}$  sec. cor. on S boundary of sec. 35, marked  $\frac{1}{4}$  on N face, from which

A fir, 24 ins. diam., bears N.35\*E., 146 lks. dist., marked  $\frac{1}{4}$  S 35 B T.

A fir, 18 ins. diam., bears N.70\*W., 22 lks. dist., marked  $\frac{1}{4}$  S 35 B T.

I obliterate marks on former bearing tree referring to sec. 2.

The course of this line is West and the distance is 40.10 chs.

Thence I run,

West on S boundary of sec. 35, T. 25 S., R. 1 W.

Ascend E slope.