

Retracement of North Boundary of T. 26 S., R. 1 W., W. M.

CHAINS

1.00

Ridge bears N and S.

Descend W slope.

18.40

Revine; course S.

Ascend SE slope.

30.00

Ridge point descending S.

Descend W slope.

40.10

The cor. of secs. 2, 3, 34 and 35, which is a basalt stone

5 x 10 x 5 ins., above ground, firmly set, marked and witnessed as described by the Surveyor General.

I re-establish this cor. as the cor. of secs. 34 and 35,

T. 25 S., R. 1 W., only, by obliterating marks on

bearing trees referring to T. 26 S.

The course of this line is West and the distance is

40.10 chs.

Land mountainous.

Soil stony, 4th rate.

Timber fir,; undergrowth hazel, vine maple and fir;

July 24, 1910.

At the cor. of secs. 34 and 35, T. 25 S., R. 1 W.

Thence I run,

West on S boundary of sec. 34, T. 25 S., R. 1 W.

Over mountainous land, heavily timbered and covered with dense undergrowth.

Descend W slope.

0.75

Creek, 5 lks. wide, course S.

Along S slope.

39.77

The $\frac{1}{4}$ sec. cor. which is a pine 10 ins. diam., marked and witnessed as described by the Surveyor General.

I re-establish this cor. in its original position as the

 $\frac{1}{4}$ sec. cor. on S boundary of sec. 34, T. 25 S., R. 1 W.,

only as follows:

The original cor. a pine 10 ins. diam., I re-mark $\frac{1}{4}$ S 34

on N side, from which