

County Surveyor's Record, Douglas County, Oregon

Retracement of North Boundary of T. 26 S., R. 1 W., W. M.

CHAINS

I re-establish this cor. in its original position as the $\frac{1}{4}$ sec. cor. on S boundary of sec. 33, T. 25 S., R. 1 W., only, as follows:

Stone, above described, already set, from which

A fir, 36 ins. diam., bears N.39*E., 18 lks. dist., marked $\frac{1}{4}$ S 33 B T.

A dogwood, 5 ins. diam., bears N.20*W., 27 lks. dist., marked $\frac{1}{4}$ S 33 B T.

I obliterate marks on former bearing tree referring to sec. 4.

The course of this line is S.89*23'W., and the distance is 40.76 chs.

From the $\frac{1}{4}$ sec. cor. I run,

West on S boundary of sec. 33, T. 25 S., R. 1 W.

Ascend E slope.

7.50 Ridge bears N and S.

Descend W slope.

40.00 The cor. of secs. 4, 5, 32 and 33, which is a fir, 9 ins. diam., marked and witnessed as described by the Surveyor General.

I re-establish this cor. as the cor. of secs. 32 and 33, T. 25 S., R. 1 W., only, by obliterating marks on bearing trees referring to T. 26 S.

The course of this line is West and the distance is 40.00 chs.

Land mountainous.

Soil, stony, 4th rate.

Timber fir; undergrowth hazel, vine maple and fir.

July 25, 1910.

At the cor. of secs. 32 and 33, T. 25 S., R. 1 W.

Thence I run,

West on S boundary of sec. 32, T. 25 S., R. 1 W.