

Resurvey of West Boundary of T. 26 S., R. 1 W., W. M.

CHAINS

Timber fir, and cedar; undergrowth vine maple, hazel and fir.

July 28, 1910.

Resurvey

At the cor. of secs. 13 and 24, T. 26 S., R. 2 W.

Thence I run,

South on a random line on E boundary of secs. 24, T. 26 S., R. 2 W.

3.05

Right bank of North Umpqua river, course W.

Set a flag on line on left bank. Then I measure a base line West 3.00 chs. to a point from which the flag bears S.49°38'E., The distance across, therefore, is $\tan 40^{\circ}22' \times \text{base}$, or 0.850×3.00 , or 2.55 chs.

Also $3.05 + 2.55$ makes

5.60

Left bank of river.

40.00

The $\frac{1}{4}$ sec. cor. is not found after careful search. Set temp. $\frac{1}{4}$ sec. cor.

80.00

The cor. of secs. 19, 24, 25 and 30 is not found after careful search. Set temp. sec. cor.

120.00

The $\frac{1}{4}$ sec. cor. between secs. 25 and 30 is not found after careful search.

Set temp. $\frac{1}{4}$ sec. cor.

175.15

The cor. of secs. 25, 30, 31 and 36, which is a decayed post, marked and witnesses as described by the Surveyor General, bears E. 4.08 chs. dist.

I re-establish the cor. in its original position as the cor. of secs. 25 and 36, T. 26 S., R. 2 W., only as follows:

Set a basalt stone 15 x 10 x 8 ins., 10 ins. in the ground for cor. of secs. 25 and 36, T. 26 S., R. 2 W., marked with 5 notches on N and 1 notch on S edge,

