

County Surveyor's Record, Douglas County, Oregon

Resurvey of West Boundary of T. 26 S., R. 1 W., W. M.

CHAINS

26 S., R. 2 W., marked $\frac{1}{4}$ on W face, from which

A madrone, 5 ins. diam., bears S.61*W., 21 lks. dist.,
marked $\frac{1}{4}$ S 36 B T.

A madrone, 5 ins. diam., bears N.47*W., 20 lks. dist.,
marked $\frac{1}{4}$ S 36 B T.

40.00 Top of ascent.

Along W slope.

55.05 The cor. of secs. 25 and 36, T. 26 S., R. 2 W.

Land mountainous.

Soil stony, 4th rate.

Timber fir and cedar.

Undergrowth vine maple, snowbrush and fir.

July 31, 1910.

Resurvey and
Retracement of South Boundary of T. 26 S., R. 1 W., W. M.

RETRACEMENT

At the closing cor. of Tps. 26 and 27 S., R. 1 W., which
is a basalt stone 5 x 12 x 8 ins., above ground, firmly
set, marked and witnessed as described by the Surveyor
General.

Thence I retrace,

East on N boundary of sec. 6, T. 27 S., R. 1 W.

30.55 The $\frac{1}{4}$ sec. cor., which is a basalt stone 5 x 18 x 5 ins.,
above ground, firmly set, marked and witnessed as
described by the Surveyor General.

The course of this line is East and the distance is
30.55 chs.

From the $\frac{1}{4}$ sec. cor. I retrace,