

County Surveyor's Record, Douglas County, Oregon

Resurvey of South Boundary of T. 26 S., R. 1 W., W. M.

CHAINS	
	<p>A fir, 10 ins. diam., bears N.6*E., 57 lks. dist., marked $\frac{1}{4}$ S 36 B T.</p>
	<p>A fir, 6 ins. diam., bears N.84*W., 12 lks. dist., marked $\frac{1}{4}$ S 36 B T.</p>
40.44	<p>The old $\frac{1}{4}$ sec. cor. which I re-establish in its original position as the $\frac{1}{4}$ sec. cor. on N boundary of sec. 1, T. 27 S., R. 1 W., only, as follows:</p> <p>I obliterate marks on N side of stone and mark $\frac{1}{4}$ on S side, from which</p> <p>A fir, 16 ins. diam., bears S.81*E., 34 lks. dist., marked $\frac{1}{4}$ S 1 B T.</p> <p>A fir, 18 ins. diam., bears S.20*W., 24 lks. dist., marked $\frac{1}{4}$ S 1 B T.</p> <p>I obliterate marks on former bearing tree referring to sec. 36.</p>
40.90	<p>A fir, 30 ins. diam., marked with 2 notches on E and W sides.</p>
55.10	<p>Cougar creek, 5 lks. wide, course N.</p>
80.00	<p>Set a conglomerate stone 16 x 10 x 5 ins., 11 ins. in the ground for cor. of secs. 35 and 36, marked with 1 notch on E and 5 notches on W edge, from which</p> <p>A fir, 20 ins. diam., bears N.76*E., 27 lks. dist., marked T 26 S R 1 W S 36 B T.</p> <p>A fir, 9 ins. diam., bears N.87*W., 10 lks. dist., marked T 26 S R 1 W S 35 B T.</p> <p>Land mountainous.</p> <p>Soil stony, 3rd and 4th rate.</p> <p>Timber fir, cedar and hemlock; undergrowth vine maple, rhododendron and yew.</p>
	<p>West on S boundary of sec. 35.</p> <p>Over mountainous land, heavily timbered and covered with dense undergrowth.</p> <p>Along N slope.</p>
0.75	<p>The old cor. of secs. 1, 2, 35 and 36, which I re-establish</p>