

Resurvey of South Boundary of T. 26 S., R. 1 W., W. M.

CHAINS	
	as the cor. of secs. 1 and 2, T. 27 S., R. 1 W., only by obliterating marks on bearing trees referring to secs. 35 and 36.
4.35	Creek, 1 lk. wide, course N. Ascend E slope.
9.10	Ravine, course NE.
25.00	Divide between North Umpqua river and Emile creek bears N and S. Descend W slope.
34.50	Creek, 2 lks. wide, course SW. Along S slope.
40.00	A fir, 8 ins. diam., for $\frac{1}{4}$ sec. cor. on S boundary of sec. 35, I mark $\frac{1}{4}$ S 35 on N side, from which A hemlock, 10 ins. diam., bears N.46*E., 21 lks. dist., marked $\frac{1}{4}$ S 35 B T. A fir, 24 ins. diam., bears N.50*W., 20 lks. dist., marked $\frac{1}{4}$ S 35 B T.
41.09	The old $\frac{1}{4}$ sec. cor. which I re-establish as the $\frac{1}{4}$ sec. cor. on N boundary of sec. 2, T. 27 S., R. 1 W., only. I obliterate marks on N face of stone and mark $\frac{1}{4}$ on S face, from which A hemlock, 8 ins. diam., bears S.56*E., 62 lks. dist., marked $\frac{1}{4}$ S 2 B T. A fir, 8 ins. diam., bears S.34*W., 16 lks. dist., marked $\frac{1}{4}$ S 2 B T. I obliterate marks on former bearing tree referring to sec. 35.
60.35	Creek, 1 lk. wide, course S.70*W.
71.55	Creek, 2 lks. wide, course S.
80.00	A fir, 48 ins. diam., for cor. of secs. 34 and 35, I mark T 26 S S 35 on NE and R 1 W S 34 on NW side, with 2 notches on E and 4 notches on W side, from which A hemlock, 5 ins. diam., bears N.31*E., 4 lks. dist., marked T 26 S R 1 W S 35 B T.