

## County Surveyor's Record, Douglas County, Oregon

## Resurvey of South Boundary of T. 26 S., R. 1 W., W. M.

CHAINS 35.00	Bluff 25 ft. high.
40.00	Set a basalt stone 18 x 12 x 10 ins., 12 ins. in the ground for $\frac{1}{4}$ sec. cor. on S boundary of sec. 33, marked $\frac{1}{4}$ on N face, from which A fir, 10 ins. diam., bears N.60*E., 25 lks. dist., marked $\frac{1}{4}$ S 33 B T. A fir, 24 ins. diam., bears N.21*W., 12 lks. dist., marked $\frac{1}{4}$ S 33 B T.
41.05	Top of bluff 60 ft. high.
41.75	Point for $\frac{1}{4}$ sec. cor. for sec. 4, T. 27 S., R. 1 W. on bluff.
41.95	The old witness cor. to the $\frac{1}{4}$ sec. cor. which I re-establish as the witness cor. to the $\frac{1}{4}$ sec. cor. on N boundary of sec. 4, T. 27 S., R. 1 W., only as follows: I obliterate marks on N face of stone and mark W C $\frac{1}{4}$ on S face, from which A fir, 14 ins. diam., bears S.30*E., 21 lks. dist., marked W C $\frac{1}{4}$ S 4 B T. A hemlock, 24 ins. diam., bears S.26*W., 7 lks. dist., marked W C $\frac{1}{4}$ S 4 B T. I obliterate marks on former bearing tree referring to sec. 33.
80.00	Point for cor. of secs. 32 and 33 falls on a basalt rock in place, 6 x 12 x 12 ins. above ground on which I cut a cross (x) at exact cor. point, with 4 notches on E and 2 notches on W of cross, from which A fir, 8 ins. diam., bears N.80*E., 14 lks. dist., marked T 26 S R 1 W S 33 B T. A fir, 10 ins. diam., bears N.65*W., 26 lks. dist., marked T 26 S R 1 W S 32 B T. Land mountainous. Soil, stony, 4th rate. Timber fir and hemlock; undergrowth, vine maple, rhododendron and hemlock.