

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 26 S., R. 1. W., W. M.

CHAINS

Point for  $\frac{1}{4}$  sec. cor. on N boundary sec. 1 falls on a conglomerate rock in place, 3 x 2 x 2 ft. above ground on which I

Cut a cross (x) at exact cor. point,  $\frac{1}{4}$  S of cross, from which

A fir, 24 ins. diam., bears S.50\*E., 39 lks. dist., marked  $\frac{1}{4}$  S 1 B T.

A cedar, 20 ins. diam., bears S.11\*W., 45 lks. dist., marked  $\frac{1}{4}$  S 1 B T.

August 13, 1910.

At the cor. of secs. 34 and 35 on the S boundary of the Tp. previously described.

Thence I run

N.0\*2'W between secs. 34 and 35.

Over mountainous land, heavily timbered and covered with dense undergrowth.

Gradually ascend S slope.

40.00 A fir, 36 ins. diam., for  $\frac{1}{4}$  sec. cor. I mark  $\frac{1}{4}$  S 34 on W and 35 on E side, from which

A fir, 18 ins. diam., bears S.29\*E., 44 lks. dist., marked  $\frac{1}{4}$  S 35 B T.

A fir, 20 ins. diam., bears S.85\*W., 56 lks. dist., marked  $\frac{1}{4}$  S 34 B T.

50.00 Low ridge bears E and W.

80.00 Set a basalt stone 15 x 8 x 8 ins., 10 ins. in the ground for cor. of secs. 26, 27, 34 and 35, marked with 1 notch on S and 2 notches on E edge, from which

A fir, 48 ins. diam., bears N.71\*E., 24 lks. dist., marked T 26 S R 1 W S 26 B T.

A hemlock, 24 ins. diam., bears S.3\*E., 50 lks. dist., marked T 26 S R 1 W S 35 B T.

A fir, 24 ins. diam., bears S.20\*W., 69 lks. dist., marked T 26 S R 1 W S 34 B T.