

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 1 W., W. M.

CHAINS	
40.00	<p>Descend N slope.</p> <p>Set a basalt stone 18 x 10 x 5 ins., 12 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W face, from which</p> <p>A fir, 12 ins. diam., bears S.3*E., 7 lks. dist., marked $\frac{1}{4}$ S 11 B T.</p> <p>A fir, 12 ins. diam., bears S.18*W., 7 lks. dist., marked $\frac{1}{4}$ S 10 B T.</p>
58.50	Ravine, course NW.
64.25	<p>Left bank of North Umpqua river, course SW.</p> <p>Set flag for observation. Also set flag on line on right bank. Then I find point on left bank from which flag on right bank bears S.89*58'W. From this point the flag on left bank bears S. 32*W., 5.60 chs. dist. The distance across therefore, is cos. 32*2' x base or 0.848 x 5.60, or 4.75 chs; also 64.25 + 4.75 makes</p>
69.00	<p>Right bank of river.</p> <p>Ascend SE slope.</p>
80.00	<p>Set a basalt stone 16 x 10 x 8 ins., 11 ins. in the ground for cor. of secs. 2, 3, 10 and 11, marked with 5 notches on S and 2 notches on E edge, from which</p> <p>A fir, 20 ins. diam., bears N.7*E., 169 lks. dist., marked T 26 S R 1 W S 2 B T.</p> <p>A fir, 36 ins. diam., bears S.5*E., 79 lks. dist., marked T 26 S R 1 W S 11 B T.</p> <p>A fir, 30 ins. diam., bears S.50*W., 87 lks. dist., marked T 26 S R 1 W S 10 B T.</p> <p>A fir, 36 ins. diam., bears N.31$\frac{1}{2}$*W., 73 lks. dist., marked T 26 S R 1 W S 3 B T.</p>
	<p>Land mountainous.</p> <p>Soil stony, 4th rate.</p> <p>Timber fir and hemlock; undergrowth vine maple, snow brush and hemlock.</p>

August 20, 1910.

