

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 1 W., W. M.

CHAINS
40.00

Set a basalt stone 12 x 12 x 10 ins., 8 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W face, from which

A fir, 12 ins. diam., bears N.65*E., 17 lks. dist., marked $\frac{1}{4}$ S 34 B T.

A fir, 28 ins. diam., bears N.21*W., 46 lks. dist., marked $\frac{1}{4}$ S 33 B T.

70.00

Divide between Emile creek and North Umpqua river bears NE and SW.

Descend NW slope.

80.00

Set a basalt stone 15 x 10 x 6 ins., 10 ins. in the ground for cor. of secs. 27, 28, 33 and 34, marked with 1 notch on S and 3 notches on E edge, from which

A fir, 10 ins. diam., bears N.65*E., 12 lks. dist., marked T 26 S R 1 W S 27 B T.

A fir, 14 ins. diam., bears S.49*E., 43 lks. dist., marked T 26 S R 1 W S 34 B T.

A fir, 24 ins. diam., bears S.15*W., 14 lks. dist., marked T 26 S R 1 W S 33 B T.

A fir, 12 ins. diam., bears N.13*W., 23 lks. dist., marked T 26 S R 1 W S 28 B T.

Land mountainous.

Soil loam, 2nd and 3rd rate.

Timber fir and hemlock; undergrowth rhododendron, vine maple and hemlock.

40.00

East on a random line between secs. 27 and 34.

Set temp. $\frac{1}{4}$ sec. cor.

80.10

Intersect N and S line 7 lks. N of cor. of secs. 26, 27 34 and 35.

Thence I run

N.89*57'W on a true line between secs. 27 and 34.

Over mountainous land, heavily timbered and covered with dense undergrowth.

Along S slope.