

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 1 W., W. M.

CHAINS 43.00	Bluff 20 ft. high.
60.25	Bluff 30 ft. high.
80.00	Set a basalt stone 15 x 10 x 8 ins., 10 ins. in the ground for cor. of secs. 21, 22, 27 and 28, marked with 2 notches on S and 3 notches on E edge, from which A fir, 20 ins. diam., bears N.23*E., 17 lks. dist., marked T 26 S R 1 W S 22 B T. A fir, 24 ins. diam., bears S.70*E., 56 lks. dist., marked T.26 S R 1 W S 27 B T. A fir, 15 ins. diam., bears S.60*W., 35 lks. dist., marked T 26 S R 1 W S 28 B T. A hemlock, 8 ins. diam., bears N.83*W., 36 lks. dist., marked T 26 S R 1 W S 21 B T. Land mountainous. Soil stony, 4th rate. Timber fir and hemlock; undergrowth vine maple and hemlock.
40.00	S.89*57'E on a random line between secs. 22 and 27. Set temp. $\frac{1}{4}$ sec. cor.
80.40	Intersect N and S line 14 lks. S of the cor. of secs. 22, 23, 26 and 27. Thence I run S.89*57'W on a true line between secs. 22 and 27. Over mountainous land, heavily timbered and covered with dense undergrowth. Along N slope.
2.10	Bluff 20 ft. high.
19.10	Creek, 2 lks. wide, course NE. Ascend NE slope.
40.20	Set a limestone 15 x 8 x 6 ins., 10 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N face, from which A fir, 18 ins. diam., bears N.72*W., 32 lks. dist., marked $\frac{1}{4}$ S 22 B T.