

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 26 S., R. 1 W., W. M.

61.90	CHAINS Creek, 1 lk. wide, in ravine, course E.
69.25	Creek, 5 lks. wide, course NE.
72.00	Ridge bears E and W.
80.00	Set a basalt stone 24 x 12 x 12 ins., 18 ins. in the ground for cor. of secs. 15, 16, 21 and 22, marked with 3 notches on S and E edges, from which A fir, 8 ins. diam., bears N.12*E., 32 lks. dist., marked T 26 S R 1 W S 15 B T. A fir, 24 ins. diam., bears S.86*E., 9 lks. dist., marked T 26 S R 1 W S 22 B T. A fir, 6 ins. diam., bears S.68*W., 16 lks. dist., marked T 26 S R 1 W S 21 B T. A fir, 16 ins. diam., bears N.57*W., 17 lks. dist., marked T 26 S R 1 W S 16 B T.  Land mountainous. Soil loam and stony, 3rd and 4th rate. Timber fir and hemlock; undergrowth rhododendron, vine maple and hemlock.
40.00	N.89*57'E on a random line between secs. 15 and 22. Set temp. $\frac{1}{4}$ sec. cor.
80.36	Intersect N and S line 50 lks. N of the cor. of secs. 14, 15, 22 and 23. Thence I run N.89*42*W on a true line between secs. 15 and 22. Over mountainous land, heavily timbered and covered with dense undergrowth. Ascend gradually.
30.00	Creek, 1 lk. wide, course N.
40.18	Set a conglomerate stone 12 x 8 x 6 ins., 8 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N face, from which A madrone, 14 ins. diam., bears N.42*W., 13 lks. dist., marked $\frac{1}{4}$ S 15 B T.