

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 1 W., W. M.

CHAINS

A maple, 5 ins. diam., bears N.24*E., 50 lks. dist.,
marked T 26 S R 1 W S 10 B T.

A fir, 40 ins. diam., bears S.19*E., 37 lks. dist.,
marked T 26 S R 1 W S 15 B T.

A chinquapin, 5 ins. diam., bears S.39*W., 45 lks.
dist., marked T 26 S R 1 W S 16 B T.

A fir, 60 ins. diam., bears N.53*W., 40 lks. dist.,
marked T 26 S R 1 W S 9 B T.

Land mountainous.

Soil loam and stony, 3rd and 4th rate.

Timber fir and hemlock; undergrowth vine maple, rhododendron
and snowbrush.

August 27, 1910.

At the cor. of secs. 9, 10, 15 and 16.

Thence I run

S.89*42'E on a random line between secs. 10 and 15.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.90 Intersect N and S line 30 lks. S of the cor. of secs. 10,
11, 14 and 15.

Thence I run

N.89*55'W on a true line between secs. 10 and 15.

Over mountainous land, heavily timbered and covered with
dense undergrowth.

Descend W slope.

14.25 Creek, 5 lks. wide, course N.

Ascend NE slope.

16.00 Creek, 1 lk. wide, course NE.

30.50 Ridge bears N and S.

Descend NW slope.

39.95 Set a basalt stone 15 x 10 x 6 ins., 10 ins. in the ground
for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N face, from which

A fir, 5 ins. diam., bears N.33*E., 8 lks. dist.,
marked $\frac{1}{4}$ S 10 B T.