

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 1 W., W. M.

CHAINS

A fir, 5 ins. diam., bears S.64*E., 16 lks. dist., marked 1/2 S 15 B T.

55.25 Bluff 25 ft. high.

55.85 Creek, 10 lks. wide, course N.

Ascend E slope.

58.75 Bluff 40 ft. high.

79.90 The cor. of secs. 9, 10, 15 and 16.

Land mountainous.

Soil, stony, 4th rate.

Timber fir and hemlock; undergrowth vine maple, rhododendron and snowbrush.

August 28, 1910.

At the cor. of secs. 9, 10, 15 and 16.

Thence I run

N.0*2'W between secs. 9 and 10.

Over mountainous land, heavily timbered and covered with dense undergrowth.

Descend ridge point to river.

13.25 Bluff 40 ft. high.

40.00 Set a basalt stone 15 x 8 x 6 ins., 10 ins. in the ground for 1/4 sec. cor., marked 1/4 on W face, from which

A hemlock, 10 ins. diam., bears S.45*E., 26 lks. dist., marked 1/4 S 10 B T.

A maple, 8 ins. diam., bears S.3*W., 24 lks. dist., marked 1/4 S 9 B T.

41.20 Left bank of North Umpqua river, course W.

Set flag on line on right bank. Then I measure a base line N.89*58'E., 3.00 chs. to a point from which the flag bears N.50*14'W. The distance across, therefore, is tan 39*48' x base, or 0.833 x 3.00, or 2.50 chs.

Also, 41.20 + 2.50 makes

Right bank of river.

