

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 1 W., W. M.

CHAINS

S.89*53'W on a true line between secs. 28 and 33.

Over mountainous land, heavily timbered and covered with dense undergrowth.

Along N slope.

26.75 Creek, 2 lks. wide, course N.

39.99 Set a basalt stone 12 x 10 x 6 ins., 8 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N face, from which

A fir, 16 ins. diam., bears N.16*E., 12 lks. dist., marked $\frac{1}{4}$ S 28 B T.

A fir, 20 ins. diam., bears S.12*W., 22 lks. dist., marked $\frac{1}{4}$ S 33 B T.

79.98 The cor. of secs. 28, 29, 32 and 33.

Land mountainous.

Soil stony, 3rd and 4th rate.

Timber fir and hemlock; undergrowth vine maple and rhododendron.

September 1, 1910.

At the cor. of secs. 28, 29, 32 and 33.

Thence I run

N.0*3'W between secs. 28 and 29.

Over mountainous land, heavily timbered and covered with dense undergrowth.

Descend N slope.

3.80 Bluff 15 ft. high.

10.75 Bluff 35 ft. high.

12.00 Bluff 25 ft. high.

40.00 Set a basalt stone 12 x 8 x 6 ins., 8 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W face, from which

A fir, 24 ins. diam., bears N.50*E., 21 lks. dist., marked $\frac{1}{4}$ S 28 B T.

A fir, 24 ins. diam., bears S.67*W., 20 lks. dist., marked $\frac{1}{4}$ S 29 B T.

50.65 Creek, 3 lks. wide, course E.