

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 26 S., R. 1 W., W. M.

CHAINS  
59.97

Set a conglomerate stone 18 x 12 x 6 ins., 12 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on N face, from which

A fir, 30 ins. diam., bears N.78\*W., 22 lks. dist., marked  $\frac{1}{4}$  S 16 B T.

A fir, 24 ins. diam., bears S.40\*E., 45 lks. dist., marked  $\frac{1}{4}$  S 21 B T.

60.25 Creek, 1 lk. wide, course S.

61.75 Creek, 1 lk. wide, course S.

62.25 Ridge point descending S.

79.94 The cor. of secs. 16, 17, 20 and 21.

Land mountainous.

Soil loam and stony, 2nd and 3rd rate.

Timber fir and hemlock; undergrowth vine maple, hemlock and hazel.

September 3, 1910.

At the cor. of secs. 16, 17, 20 and 21.

Thence I run

N.0\*3\*W between secs. 16 and 17.

Over mountainous land, heavily timbered and covered with dense undergrowth.

Ascend S slope.

14.00 Ridge point descending W.

Along W slope.

23.00 Creek, 2 lks. wide, course W.

Ascend S slope.

38.00 Ridge bears E and W.

Descend N slope to river.

40.00 Set a basalt stone 12 x 12 x 10 ins., 8 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on W face, from which

A hemlock, 5 ins. diam., bears S.85\*E., 11 lks. dist., marked  $\frac{1}{4}$  S 16 B T.

A hemlock, 6 ins. diam., bears N.24\*W., 11 lks. dist., marked  $\frac{1}{4}$  S 17 B T.