

Subdivisions of T. 26.S., R. 1 W., W. M.

CHAINS
11.66

Right bank of North Umpqua river, course SW.

Set flag on line on left bank. Also at right angles to line course S.0°20'E., set flag for triangulation point on left bank. From flag on line on left bank, triangulation point bears S.43°42'W., 5.17 chs. dist. The distance across, therefore, is $\sin 44^{\circ}2'$ x base, or 0.695×5.17 , or 3.59 chs. Also, $11.66 + 3.59$ makes

15.25 Left bank of river.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.12 Intersect N and S line 32 lks. N of the cor. of secs. 9, 10, 15 and 16.

Thence I run

S.89°54'W on a true line between secs. 9 and 16.

Over mountainous land, heavily timbered and covered with dense undergrowth.

0.25 Ridge bears N and S.

Descend NW slope.

13.00 Ravine, course NW.

Ascend E slope.

18.65 Ridge point descending N.

Descend NW slope.

21.20 Ravine, course N.

Ascend E slope.

27.25 Ridge point descending N.

Descend W slope.

40.06 Set a granite stone 12 x 8 x 6 ins., 8 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N face, from which

A hemlock, 7 ins. diam., bears N.11°E., 20 lks. dist., marked $\frac{1}{4}$ S 9 B T.

A cedar, 10 ins. diam., bears S.40°W., 35 lks. dist., marked $\frac{1}{4}$ S 16 B T.

41.15 Creek, 3 lks. wide, course N,

