

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 1 W., W. M.

CHAINS
80.00

A fir, 16 ins. diam., for cor. of secs. 4, 5, 8 and 9, I mark T 26 S S 4 on NE, R 1 W S 9 on SE, S 8 on SW and S 5 on NW side, with 5 notches on S and 4 notches on E side, from which

A fir, 10 ins. diam., bears N.31*E., 11 lks. dist., marked T 26 S R 1 W S 4 B T.

A fir, 10 ins. diam., bears S.63*E., 10 lks. dist., marked T 26 S R 1 W S 9 B T.

A fir, 6 ins. diam., bears S.13*W., 8 lks. dist., marked T 26 S R 1 W S 8 B T.

A fir, 8 ins. diam., bears N.69*W., 15 lks. dist., marked T 26 S R 1 W S 5 B T.

Land mountainous.

Soil loam and stony, 2nd and 4th rate.

Timber fir; undergrowth vine maple and arrowwood.

N.89*54'E on a random line between secs. 4 and 9.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.20 Intersect N and S line 16 lks. N of the cor. of secs. 3, 4, 9 and 10.

Thence I run

N.89*59'W on a true line between secs. 4 and 9.

Over mountainous land, heavily timbered and covered with dense undergrowth.

Along S slope.

6.00 Creek, 1 lk. wide, course S.

19.50 Rocky ridge bears N and S.

30.00 Descend steep W slope.

40.10 Set a conglomerate stone 15 x 8 x 6 ins., 10 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on N face, from which

A maple, 10 ins. diam., bears N.14*E., 47 lks. dist., marked $\frac{1}{4}$ S 4 B T.

A maple, 7 ins. diam., bears S.74*W., 14 lks. dist., marked $\frac{1}{4}$ S 9 B T.