

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 1 W., W. M.

CHAINS
112.70

Fairview creek, 8 lks. wide, course SE.

Ascend SW slope.

119.60

Intersect N boundary of the Tp. 22.90 chs. E of the cor. of secs. 31 and 32, T. 25 S., R. 1 W., previously described.

Set a conglomerate stone 15 x 10 x 6 ins., 10 ins. in the ground for closing cor. of secs. 4 and 5, marked CC on S, with 4 grooves on E and 2 grooves on W face, from which

A fir, 30 ins. diam., bears S.82*E., 18 lks. dist., marked T 26 S R 1 W S 4 B T.

A fir, 12 ins. diam., bears S.56*W., 17 lks. dist., marked T 26 S R 1 W S 5 B T.

Land mountainous.

Soil stony, 4th rate.

Timber fir; undergrowth vine maple and arrowwood.

The length of the N boundary of sec. 4 is 79.80 chs.

Therefore at point midway on this line, 22.60 chs. E of the $\frac{1}{4}$ sec. cor. on S boundary of sec. 32, T. 25 S., R. 1 W., I establish $\frac{1}{4}$ sec. cor. on N boundary of sec. 4, as follows:

Set a basalt stone 15 x 8 x 8 ins., 10 ins. in the ground for $\frac{1}{4}$ sec. cor. on N boundary of sec. 4, marked $\frac{1}{4}$ on S face, from which

A fir, 20 ins. diam., bears S.19*E., 42 lks. dist., marked $\frac{1}{4}$ S & B T.

A fir, 18 ins. diam., bears S.1*W., 44 lks. dist., marked $\frac{1}{4}$ S 4 B T.

September 7, 1910.

At the cor. of secs. 31 and 32, on the S boundary of the Tp., previously described.

Thence I run