

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 26 S., R. 1 W., W. M.

CHAINS

The West boundary of sec. 31 is 80.00 chs. Therefore at point midway on this line,  $2.02\frac{1}{2}$  chs. S of the  $\frac{1}{4}$  sec. cor. on E boundary of sec. 36, T. 26 S., R. 2 W., I establish  $\frac{1}{4}$  sec. cor. on W boundary of sec. 31, as follows:

Set a conglomerate stone 12 x 8 x 6 ins., 8 ins. in the ground for  $\frac{1}{4}$  sec. cor. on W boundary of sec. 31, marked  $\frac{1}{4}$  on E face, from which

A fir, 16 ins. diam., bears N.24\*E., 44 lks. dist., marked  $\frac{1}{4}$  S 31 B T.

A cedar, 9 ins. diam., bears S.22\*E., 44 lks. dist., marked  $\frac{1}{4}$  S 31 B T.

September 10, 1910.

At the cor. of secs. 29, 30, 31 and 32.

Thence I run

N.0\*4'W between secs. 29 and 30.

Over mountainous land, heavily timbered and covered with dense undergrowth.

Ascend steep, rocky, S slope.

6.80 Bluff 20 ft. high.

16.75 Divide between Emile creek and North Umpqua river bears E and W.

Descend steep N slope.

34.00 Creek, 1 lk. wide, course NW.

Along W slope.

40.00 Set a conglomerate stone, 18 x 12 x 4 ins., 12 ins. in the ground for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on W face, from which

A fir, 15 ins. diam., bears N.53\*E., 71 lks. dist., marked  $\frac{1}{4}$  S 29 B T.

A cedar, 15 ins. diam., bears N.64\*W., 79 lks. dist., marked  $\frac{1}{4}$  S 30 B T.

56.25 Ridge bears N.15\*W. and S.15\*E.