

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 26 S., R. 1 W., W. M.

CHAINS	<p>A cedar, 30 ins. diam., bears S.29*E., 55 lks. dist., marked <math>\frac{1}{4}</math> S 30 B T.</p>
	September 12, 1910.
	At the cor. of secs. 19, 20, 29 and 30.
	Thence I run
	N.0*4'W between secs. 19 and 20.
	Over mountainous land, heavily timbered and covered with dense undergrowth.
	Ascend SW slope.
7.75	Ridge bears NE and SW.
	Descend gradually.
40.00	Set a basalt stone 12 x 8 x 6 ins., 8 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W face, from which
	A chinquapin, 10 ins. diam., bears N.38*E., 37 lks. dist., marked $\frac{1}{4}$ S 20 B T.
	A fir, 40 ins. diam., bears S.81*W., 15 lks. dist., marked $\frac{1}{4}$ S 19 B T.
53.50	Creek, 1 lk. wide, course NW.
56.00	Creek, 3 lks. wide, course NW.
	Ascend SW slope.
61.75	Creek, 1 lk. wide, course W.
70.00	Ridge point descending NW.
	Descend N slope.
75.65	Bluff 20 ft. high.
80.00	Point for cor. of secs. 17, 18, 19 and 20 falls on a basalt rock in place, 10 x 12 x 8 ins., above ground, on which I cut a cross (x) at exact cor. point, with 3 notches S and 5 notches E of cross, from which
	A cedar, 16 ins. diam., bears N.42*E., 50 lks. dist., marked T 26 S R 1 W S 17 B T.
	A fir, 30 ins. diam., bears S.82 $\frac{1}{2}$ *E., 100 lks. dist., marked T 26 S R 1 W S 20 B T.