

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 1 W., W. M.

CHAINS
79.00

Intersect W boundary of the Tp. 5.05 chs. S. 1*E., of the cor. of secs. 1 and 12, T. 26 S., R. 2 W., previously described.

Set a basalt stone 16 x 12 x 12 ins., 11 ins. in the ground for closing cor. of secs. 6 and 7, marked CC on E, with 1 groove on N and 5 grooves on S face, from which

A chinquapin, 10 ins. diam., bears N.72*E., 44 lks. dist., marked T 26 S R 1 W S 6 B T.

A madrone, 6 ins. diam., bears S.25*E., 28 lks. dist., marked T 26 S R 1 W S 7 B T.

Land mountainous and level.

Soil loam and stony, 2nd and 4th rate.

Timber fir and hemlock; undergrowth vine maple, fir and chinquapin.

The length of the W boundary of secs. 7 is 80.02 chs.

Therefore at point midway on this line, 4.13 chs., S.0*48'W., of the $\frac{1}{4}$ sec. cor. on E boundary of sec. 12, T. 26 S., R. 2 W., I establish $\frac{1}{4}$ sec. cor. on W boundary of sec. 7, as follows:

Set a basalt stone 16 x 12 x 10 ins., 11 ins. in the ground for $\frac{1}{4}$ sec. cor. on W boundary of sec. 7, marked $\frac{1}{4}$ on E face, from which

A chinquapin, 15 ins. diam., bears N.28*E., 73 lks. dist., marked $\frac{1}{4}$ S 7 B T.

A madrone, 5 ins. diam., bears S.69*E., 43 lks. dist., marked $\frac{1}{4}$ S 7 B T.

At a point on the W boundary of sec. 6, 40.00 chs. North of the closing cor. of secs. 6 and 7, 5.25 chs. S of the $\frac{1}{4}$ sec. cor. on E boundary of sec. 1, T. 26 S., R. 2 W., I establish $\frac{1}{4}$ sec. cor. on W boundary of sec. 6, as follows: