

County Surveyor's Record, Douglas County, Oregon

East Bdy. of T. 26 S., R. 3 W.

CHAINS

A R fir, 7 ins. diam., bears S.5*W., 57 lks. dist.

A R fir, 40 ins. diam., bears S.36*E., 64 lks. dist.

A maple, 2 ins. diam., bears N.35*E., 42 lks. dist.

A maple, 2 ins. diam., bears N.51*W., 26 lks. dist.

A mound of stone around the post

Land, exceedingly rough, 3rd rate

Timber, fir, cedar, oak & laurel

North Bdy. of T. 27 S., R. 2 W. as Surveyed by
Samuel C. Flint, Deputy Surveyor, under Cont. No. 459
Dated August 3, 1882

Before commencing this survey, I test my compass on the
line established last night and find it correct.

I began at the corner to Tps. 26 & 27 S. Rs. 2 & 3 W, which
is a fir post 4 ins. sq. marked T 27 S R 2 W S 6 on SE,
T 27 S R 3 W S 1 on SW, T 26 S R 3 W S ³/₂₆ on NW, T 26
S R 2 W S 31 on NE, faces with 6 notches on each edge
of post N, S, E and W from which

A laurel, 12 ins. diam., bears S.5*E., 66 lks. dist.

Marked T 27 S R 2 W S 6 B T

A fir, 16 ins. diam., bears S.38*W., 7 lks. dist.

Marked T 27 S R 3 W S 1 B T

A laurel, 5 ins. diam., bears N.25*W., 59 lks. dist.

Marked T 26 S R 3 W S 36 B T

(No tree near in sec. 31)

Thence I run

East on true line bet. secs. 6 & 31

Va. 19*10'E.

6.00 Summit of ridge, course N & S
25.00 Spring branch 2 lks. wide course S
33.00 Summit of mountain
40.00 Set laurel post, 3 ft. long, 3 ins. sq. 24 ins. in the
ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S on N and S faces