

## County Surveyor's Record, Douglas County, Oregon

North Bdy. of T. 27 S., R. 2 W.

CHAINS  
80.00

Set a chinquapin post, 4 ft. long, 4 ins. sq. 24 ins. in the ground for cor. to secs. 1, 6, 31 and 36 and marked T 26 S S 31 on NE, R 1 W S 6 on SE, T 27 S S 1 on SW, R 2 W S 36 on NW faces, with 6 notches on N, S, E & W edges, from which

A laurel, 7 ins. diam., bears N.45\*E., 28 lks. dist.

Marked T 26 S R 1 W S 31 B T

A fir, 6 ins. diam., bears S.60\*E., 31 lks. dist.

Marked T 27 S R 1 W S 6 B T

A fir, 40 ins. diam., bears S.74\*W., 25 lks. dist.

Marked T 27 S R 2 W S 1 B T

A fir, 24 ins. diam., bears N.3\*W., 23 lks. dist.

Marked T 26 S R 2 W S 36 B T

This mile is rough, rocky, and mountainous,

Densely covered with fir, cedar, hemlock and laurel

Thick undergrowth of vine-maple, hazel and huckleberry.

August 18, 1882

Subdivisions of T. 26 S., R. 2 W.  
Surveyed by John A. McQuinn Deputy Surveyor  
Under Contract No. 466  
Dated April 5, 1883

I commenced at the cor. to secs. 1, 2, 35 and 36 on the South bdy. which is a post, 4 ft. long, 4 ins. sq. firmly set in the ground marked T 26 S S 36 on NE, R 2 W S 1 on SE, T 27 S S 2 on S W, S 35 on NW faces, with 1 notch on E and 5 notches on W edges, from which

A laurel, 8 ins. diam., bears N.55\*E., 30 lks. dist.

Marked T 26 S R 2 W S 36 B T

A laurel, 10 ins. diam., bears S.70\*E., 30 lks. dist.

Marked T 27 S R 2 W S 1 B T

A fir, 12 ins. diam., bears S.30\*W., 24 lks. dist.

Marked T 27 S R 2 W S 2 B T

A fir, 12 ins. diam., bears N.14\*W., 14 lks. dist.

Marked T 26 S R 2 W S 35 B T