

Retracement-Reestablishment  
Portion of W. Bdy. of T. 26 S., R. 2 W.

CHAINS

and decayed; all traces of the cor. have disappeared.

I re-establish it in its original position, as follows:

Set a fir post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  S 1 on W. face and 6 on E. face, witnessed by the original bearing tree as follows:

A red fir, 24 ins. diam., bears S.88°E., 22 lks. dist. Marked  $\frac{1}{4}$  S B T

The true course and distance of this line is N.0°09'E., 40.27 chs.

Thence, from the  $\frac{1}{4}$  sec. cor., I run

North, counting distance from the sec. cor.

Descend along steep NW slope

59.44 Head of a ravine, course W; ascend

66.23 Summit of ascent on W slope; descend

80.32 Intersect the point for the cor. of Tps. 25 and 26 S., Rs. 2 and 3 W., located by reference to the SE. bearing tree and further identified by a mound of stone as described by the surveyor general; all other traces of the cor. have disappeared. I re-establish this cor. in its original position, as follows:

Set a basalt stone, 24x10x10 ins., 18 ins. in the ground, for cor. of Tps. 25 and 26 S., Rs. 2 and 3 W., marked with 6 notches on each edge and rebuild the old mound of stone around cor.; from which

A fir, 14 ins. diam., bears N.31°E., 36 lks. dist.

Marked T 25 S R 2 W S 31 B T

A fir, 40 ins. diam., bears S.36°E., 64 lks. dist.

Marked T 26 S R 2 W S 6 B T (Original bearing tree)

A laurel, 5 ins. diam., bears S.85°W., 29 lks. dist.

Marked T 26 S R 3 W S 1 B T

A fir, 10 ins. diam., bears N.22°W., 31 lks. dist.

Marked T 25 S R 3 W S 36 B T