

Retracement-Reestablishment
Portion of S. Bdy. of T. 26 S., R. 2 W.

WEST COAST PRINTING & BINDING CO., PORTLAND 18700

CHAINS

A fir, 24 ins. diam., bears N.40°E., 21 lks. dist.
 Marked T 27 S R 2 W S 34 B T (Original bearing tree)
 A laurel, 8 ins. diam., bears S.78°30'E., 33 lks.
 dist. Marked T 27 S R 2 W S 3 B T
 A fir, 36 ins. diam., bears S.78°30'W., 76 lks. dist.
 Marked T 27 S R 2 W S 4 B T
 A fir, 30 ins. diam., bears N.72°W., 33 lks. dist.
 Marked T 26 S R 2 W S 33 B T (Original bearing
 tree)

Elevation at this cor. 2670 ft.

The true course and distance of this line from the $\frac{1}{4}$ sec.
 cor. is N.89°37'E., 39.72 chs.

Land, hilly, on general S. slope of mountain

Soil, dark clayey loam free from rock in large part; 2nd
 rate

Timber, heavy growth of fir and cedar

Undergrowth, thicket of fir, laurel, vine maple and salal

Cor. of secs. 3, 4, 33 and 34, on the South Bdy. of the
 Tp.

Thence I run

East, retracing the S. bdy. of sec. 34

Ascend through heavy timber and dense undergrowth

2.00 Top of ridge, bears N. and S.; begin rapid descent on SE.
 slope

18.54 Stream, 6 lks. wide, course SE., at bottom of deep, rocky
 canyon. Elevation 2100 ft.

Ascend steep slope

26.00 Ascend steep rocky SW slope through old deadening with
 scattering fir timber and dense laurel and fir under-
 growth.

38.68 Fall 44 lks. S. of the point for the $\frac{1}{4}$ sec. cor., located
 by reference to the bearing trees, as described by the
 surveyor general; all other traces of the cor. have