

Retracement-Reestablishment  
Portion of S. Bdy. of T. 26 S., R. 2 W.

CHAINS

disappeared. I re-establish this cor. in its original position as follows:

Set a basalt stone, 20x10x8 ins., 15 ins. in the ground, for  $\frac{1}{4}$  sec. cor., marked  $\frac{1}{4}$  on N. face, witnessed by the original bearing trees, as follows:

A fir, 20 ins. diam., bears S.10\*W., 30 lks. dist.

Marked  $\frac{1}{4}$  S B T

A fir, 18 ins. diam., bears N.10\*W., 15 lks. dist.

Marked  $\frac{1}{4}$  S B T

Elevation at this cor. 2700 ft.

The true course and distance of this line is N.89\*21'E., 38.68 chs.

I continue my line East from the  $\frac{1}{4}$  sec. cor., counting distance from sec. cor.

Ascend steep rocky SW slope

44.80 Top of rocky spur, slopes S. Elevation 2900 ft.

Descend steep slope through dense fir undergrowth

52.28 Stream, 4 lks. wide, course S., at bottom of canyon.

Ascend over moderate SW slope through fir timber and dense undergrowth

78.50 Trail, bears SE and NW, at top of ascent on S. slope

78.55 Fall 13 lks. S. of cor. of secs. 2, 3, 34 and 35, which is a post, nearly decayed, witnessed by the two westerly bearing trees and stumps of the other trees described by the surveyor general. I destroy this cor. and re-establish it in the same place, as follows:

Set a basalt stone, 13x8x8 ins., 8 ins. in the ground, for cor. to secs. 2, 3, 34 and 35, marked with 2 notches on E. and 4 notches on W. edge; from which

A laurel, 7 ins. diam., bears N.57\*E., 71 lks. dist.

Marked T 26 S R 2 W S 35 B T

A laurel, 7 ins. diam., bears S.82\*E., 84 lks. dist.

Marked T 27 S R 2 W S 2 B T