

Retracement-Reestablishment  
E. Bdy. of Secs. 1, 12 and 13, T. 26 S., R. 2 W.

CHAINS	
	North, retracing the E. bdy. of sec. 1.
	Descend through dense undergrowth
.40	Stream, 1 lk. wide, course E.
8.90	Stream, 2 lks. wide, course SE
20.00	Enter heavy growth of fir timber and dense rhododendron underbrush; ascend gently on SW slope
40.56	Intersect the $\frac{1}{4}$ sec. cor. of sec. 1, which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general.
	Elevation at this cor. 3800 ft.
	The true course and distance of this line is North, 40.56 chs.
	I continue my line North from the $\frac{1}{4}$ sec. cor., counting distance from the sec. cor.
59.00	Summit of ascent; begin gradual descent on Easterly slope
79.73	Intersect the point for the cor. of Tps. 25 and 26 S., R. 2 W., located by reference to the bearing trees as described by the surveyor general; all traces of the cor. have disappeared. I re-establish this cor. in its original position, as follows:
	Set a basalt stone, 14x10x6 ins., 9 ins. in the ground, for cor. of Tps. 25 and 26 S., R. 2 W., marked with 6 notches on the N. and W. edges, witnessed by the original bearing trees, as follows:
	A fir, 30 ins. diam., bears N.85*E., 116 lks. dist. Marks obliterated
	A pine, 16 ins. diam., bears S.55*E., 45 lks. dist. Marks obliterated
	A pine, 16 ins. diam., bears S.60*W., 66 lks. dist. Marked T 26 S R 2 W S 1 B T
	A fir, 36 ins. diam., bears N.68*W., 138 lks. dist. Marked T 25 S R 2 W S 36 B T
	Elevation at this cor. 3900 ft.