

Retracement-Reestablishment of N. Bdy. of T. 26 S., R. 2 W.

CHAINS

The true bearing of the North Bdy. of this township, from the cor. of secs. 1 and 2 to the $\frac{1}{4}$ sec. cor. on the N. bdy. of sec. 4, is N.89°40'W., 196.15 chs., making each half mile thereof 39.23 chs. in length, or a proportional shortage of 77 lks. and a correction of 8 lks. North per half mile, counting from the cor. of secs. 1 and 2.

December 21, 1913.

December 22: I re-establish the missing corners on N. lines of secs. 2 and 3 on due line and at proportional distances, as follows:

From the temp. $\frac{1}{4}$ sec. cor. on N. line of sec. 2, I set off 77 lks. S.89°47'E. and 8 lks. N. and

Set a basalt stone, 14x12x8 ins., 9 ins. in the ground, for $\frac{1}{4}$ sec. cor. on N. line of sec. 2 only, marked $\frac{1}{4}$ on S. face; from which

A fir, 12 ins. diam., bears S.60°E., 34 lks. dist.

Marked $\frac{1}{4}$ S 2 B T

A fir, 14 ins. diam., bears S.44°E., 42 lks. dist.

Marked $\frac{1}{4}$ S 2 B T

Cougar Peak bears S.7°30'W.

From temp. cor. of secs. 2 and 3 on N. bdy. of Tp., I set off 154 lks. S.89°47'E. and 16 lks. N. and

Set a basalt stone, 16x10x7 ins., 10 ins. in the ground, for cor. of secs. 2 and 3 only, marked with 2 notches on the E. and 4 notches on the W. edges; from which

A rock in place, 3 $\frac{1}{2}$ ft. x 4 ft. x 3 ft. high, bears S.20°E., 54 lks. dist., marked on NW. face: T 26

S R 2 W S 2 B O

A fir, 14 ins. diam., bears S.82°30'W., 256 lks. dist.

Marked T 26 S R 2 W S 3 B T

Illick's cabin bears S.4°30'W., about 20.00 chs.

Soper's point bears S.68°E., about 22.00 chs.