

Resurvey of Portion of East Bdy., T. 26 S., R. 2 W.

CHAINS	
	Over mountainous land, through dense timber and undergrowth. Ascend steep S. slope.
10.00	Spur, slopes SW; ascend SW slope
26.53	The $\frac{1}{4}$ cor. of sec. 31, T. 26 S., R. 1 W., established by Deputy Mensch, which is a conglomerate stone, 12x8x6 ins. firmly set, marked and witnessed as described by the surveyor general, bears N.89*42'W., 74 lks. dist. To this point I now move the original stone, which I set 8 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 31, marked $\frac{1}{4}$ on E face; from which <div style="margin-left: 40px;">A fir, 18 ins. diam., bears N.12*E., 56 lks. dist. Marked $\frac{1}{4}$ S 31 B T</div> <div style="margin-left: 40px;">A fir, 30 ins. diam., bears S.27*E., 19 lks. dist. Marked $\frac{1}{4}$ S 31 B T</div> I destroy marks on bearing trees at former cor.
27.86	(Midpoint) Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 36, with brass cap marked <div style="margin-left: 100px;"> $\frac{1}{4}$ S36 1916 </div> from which <div style="margin-left: 40px;">A fir, 24 ins. diam., bears S.87*W., 49 lks. dist. Marked $\frac{1}{4}$ S 36 B T</div> <div style="margin-left: 40px;">A fir, 30 ins. diam., bears N.7*W., 23 lks. dist. Marked $\frac{1}{4}$ S 36 B T</div> I destroy the corresponding cor. of the rejected revision survey and marks on bearing trees. The cor. established by Deputy Mensch for the $\frac{1}{4}$ cor. of sec. 36, which is a basalt stone, 15x12x4 ins., firmly set, marked and witnessed as described by the surveyor general, bears N.43*15'W., 1.06 chs. dist. I now destroy this corner and marks on bearing trees.