

Resurvey of Portion of East Bdy., T. 26 S., R. 2 W.

CHAINS

Descend NW slope

9.00 Creek, 2 lks. wide, course W.

9.80 Point of spur, slopes W.

10.50 Creek, 1 lk. wide, course SW.; ascend S. slope

10.54 To a point from which the old closing cor. of secs. 30 and 31, T. 26 S., R. 1 W. (established by Deputy Mensch in 1910, which is a basalt stone, 15x8x6 ins., firmly set, marked and witnessed as described by the surveyor general) bears S.89°24'E., 36 lks. dist.

35.85 High ridge, divide bet. Emile Creek and North Umpqua River bears E and W.; descend steep N. slope

43.18 Intersect the original $\frac{1}{4}$ sec., established by Deputy McQuinn in 1883; this cor. is a hemlock post, partly burned, has evidently fallen over and been recently re-set, but at proper point as shown by the bearing trees, which are as described by the surveyor general.

I now perpetuate this cor. by setting an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 25 only, in place of the old post, now too badly delapidated for further use, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \text{S25} \\ 1916 \end{array}$$

from which

A hemlock, 8 ins. diam., bears S.58°W., 37 lks. dist.

Marked $\frac{1}{4}$ S 25 B T

A hemlock, 10 ins. diam., bears N.55°W., 24 lks. dist.

Marked $\frac{1}{4}$ S 25 B T

I destroy the corresponding cor. of the rejected revision survey and marks on bearing trees.

The cor. established by Deputy Mensch in 1910 as the $\frac{1}{4}$ cor. of said sec. 25 (which is a basalt stone, 15x8x6 ins.,