

Resurvey of Portion of East Bdy., T. 26 S., R. 2 W.

CHAINS	<p>1910, which is a basalt stone, 15x8x6 ins., firmly set, marked and witnessed as described by the surveyor general) bears W., 72 lks. dist.</p>
15.35	Creek, 2 lks. wide, course NE.
24.85	Spur, slopes NE
27.00	Ravine, course NE
35.00	Spur, slopes NE
39.75	Begin descent of precipitous NE slope
43.30	<p>Top of bluff, 150 ft. high, bears NW. and SE. As true point for $\frac{1}{4}$ cor. of sec. 19 falls on bluff where a permanent cor. cannot be established; I therefore, at this point</p> <p>Set a basalt stone, 14x10x6 ins., 10 ins. in the ground, for witness cor. to the $\frac{1}{4}$ cor. of sec. 19, T. 26 S., R. 1 W., marked W C $\frac{1}{4}$ on E. face; from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N.70*E., 26 lks. dist. Marked W C $\frac{1}{4}$ S 19 B T</p> <p style="padding-left: 40px;">A cedar, 9 ins. diam., bears S.24*E., 17 lks. dist. Marked W C $\frac{1}{4}$ S 19 B T</p> <p>Descend bluff.</p>
45.41	<p>True point for $\frac{1}{4}$ cor. of sec. 19 from which the old $\frac{1}{4}$ cor. sec. 19, T. 26 S., R. 1 W., established by Mensch (which is a basalt rock in place, marked and witnessed as described by the surveyor general) bears W., 64 lks. dist. I now destroy this cor. and marks on bearing trees.</p>
45.70 $\frac{1}{2}$	<p>True point (midpoint bet. McQuinn cors.) for $\frac{1}{4}$ cor. of sec. 24 falls on bluff where a permanent cor. cannot be established; therefore at</p>
46.31	<p>Foot of bluff.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for witness cor. to the $\frac{1}{4}$ cor. of sec. 24, with brass cap marked</p> <div style="text-align: center; margin: 10px 0;"> $\frac{1}{4}$ S24 WC 1916 </div> <p>from which</p> <p style="padding-left: 40px;">A protruding point of bluff (basalt rock) bears S.51*W., 6 lks. dist., marked B O $\frac{1}{4}$ S24 W C with cross (X) at exact bearing point.</p>