

## Resurvey of Portion of East Bdy., T. 26 S., R. 2 W.

CHAINS

A fir, 48 ins. diam., bears N.6\*W., 54 lks. dist.

Marked W C  $\frac{1}{2}$  S 24 B T

I destroy the corresponding cor. of rejected revision survey and marks on bearing trees.

The witness  $\frac{1}{4}$  cor. of sec. 24, established by Mensch in 1910, which is marked by a cross on a basalt rock, witnessed as described by the surveyor general, bears S.47\*W., 86 lks. dist. I now destroy this cor.; also marks on bearing trees.

Continue descent along gradual NE. slope

53.25 Spur, slopes NE

56.15 Creek, 5 lks. wide, course NE

65.75 Spur, slopes E.

81.00 Begin descent of precipitous N. slope to North Umpqua River

85.50 Left bank of North Umpqua River, course W.

86.56 True point for closing cor. of secs. 18 and 19, T. 26 S., R. 1 W. falls in river.

The witness cor. to this closing cor., established by Deputy Mensch in 1910 (which is marked by a cross on face of rock bluff, witnessed as described by the surveyor general) bears E., 10.24 chs. dist.

89.00 Right bank of river; ascend steep S. slope

91.41 Intersect the original McQuinn cor. established in 1883, as the cor. of secs. 13, 18, 19 and 24 and reestablished 1910 by Deputy Mensch as the cor. of secs. 13 and 24 only.

This cor. is a basalt stone, 4x10x8 ins. above ground, firmly set, marked and witnessed as described by the surveyor general.

Land, mountainous; soil, stony clay loam, 3rd rate.

Timber, fir, hemlock, cedar, and sugar pine

Undergrowth, hemlock, rhododendron, vine maple & huckleberry

Retracement Portion of South and West Boundaries;  
Retracement-Resurvey Portion of Subdivisional Lines  
and  
Metes and Bounds Survey of Tracts 37 and 38  
of

Township No. 26 South, Range No. 2 West  
Also Report on Conditions along the North Boundary of  
Tp. 26 S., R. 2 W., and along the E. Bdry., the West Bdry.  
and Certain Interior lines of Tp. 25 S., R. 2 W. Executed  
By Fred Mensch, U. S. Surveyor, under Special  
Instructions Dated May 25, 1916, April 16, 1918.