

## Retracement of Portion of S. and W. Bdrs. of T. 26 S., R. 2 W.

CHAINS	
40.13	Intersect the $\frac{1}{4}$ sec. cor., established by Deputy Flint in 1882 and reestablished by U. S. Surveyor Collier in 1913, which is a cedar post, 3 ins. sq. 12 ins. above ground, firmly set, marked $\frac{1}{4}$ S 36 on N and 1 on S face, from which
	A fir, 20 ins. diam., bears S.50*W., 9 lks. dist.
	Marked $\frac{1}{4}$ S B T
	A cedar 16 ins. diam., bears N.30*W., 35 lks. dist.
	Marked $\frac{1}{4}$ S B T
	(Original bearing trees of Flint Survey)
	Thence
	S.88*36'W., continuing the measurement
50.00	Creek, 9 lks. wide, course SW
62.00	Begin descent of steep SW slope
72.70	Creek, 3 lks. wide, course SW, ascend SE slope
74.05	Creek, 2 lks. wide, course S
80.01	Intersect the cor. of secs. 1, 2, 35 and 36, established
	by Deputy Flint in 1882 and reestablished by U. S. Surveyor Collier in 1913, which is a basalt stone, 5x8x7
	ins. above ground, firmly set, marked with 1 notch on E.
	and 5 notches on W edge, from which
	A fir, 10 ins. diam., bears N.39*30'E., 18 lks. dist.
	Marked T 26 S R 2 W S 36 B T
	A laurel, 10 ins. diam., bears S.70*E., 30 lks. dist.
	Marked T 27 S R 2 W S 1 B T (Orig. B.T.)
	A fir, 20 ins. diam., bears S.30*W., 24 lks. dist.
	Marked T 27 S R 2 W S 2 B T (Orig. B.T.)
	The original bearing tree on NW, a fir, 20 ins. diam.,
	which bears from the cor. N.14*W., 14 lks. dist., is
	not in the section to which it refers; therefore, I ob-
	literate marks on this tree and take new bearing tree
	in sec. 35 as follows:
	A fir, 24 ins. diam., bears N.30*W., 52 lks. dist.
	Marked T 26 S R 2 W S 35 B T
	Land, mountainous
	Soil, stony clay loam, 3rd rate