

Retracement of Portion of S. and W. Bdrs. of T. 26 S., R. 2 W.

CHAINS	
	<p>Timber, fir, hemlock and cedar</p> <p>Undergrowth, hazel, vine-maple, arrowwood and fir</p>
	<p>S.88*22'W., on S. Bdy. of Sec. 35</p> <p>Over mountainous land, through dense timber and undergrowth</p> <p>Along S. slope</p>
1.00	Creek, 1 lk. wide, course SE, ascend SE slope
11.00	Ascend bluff, 25 ft. high, bears NE and SW
24.00	High spur, slopes S; descend SW slope
31.00	Begin steep descent into canyon of creek
36.40	Creek, 10 lks. wide, in canyon, course S; ascend steep E slope
39.84	<p>Intersect the $\frac{1}{4}$ sec. cor, established by Deputy Flint in 1882 and reestablished by U. S. Surveyor Collier in 1913, which is a basalt stone, 5x10x8 ins. above ground, firmly set, marked $\frac{1}{4}$ on N face, from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S.65*E., 42 lks. dist. Marked $\frac{1}{4}$ S B T. (Orig. tree of Flint survey)</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears N.4*W., 45 lks. dist. Marked $\frac{1}{4}$ S 35 B T</p> <p>Thence</p> <p>S.88*38'W., continuing the measurement</p>
40.10	Ascend bluff, 15 ft. high, bears N and S
44.00	Top of steep slope, continue ascent
45.50	A barn bears North, 35 lks. dist.
46.00	A cabin bears North, 3.00 chs. dist.
46.90	Trail, bears NE and SW
55.70	Creek, 1 lk. wide, course SE
79.83	<p>Intersect the cor. of secs. 2, 3, 34 and 35, established by Deputy Flint in 1882 and reestablished by U. S. Sur- veyor Collier in 1913, which is a basalt stone, 5x8x8 ins. above ground, firmly set, marked with 2 notches on E. and 4 notches on W edge, from which</p>