

Retracement of Portions of S. and W. Edrs. of T. 26 S., R. 2 W.

CHAINS	<p>A laurel, 7 ins. diam., bears N.57*E., 71 lks. dist. Marked T 26 S R 2 W S 35 B T</p> <p>A laurel, 7 ins. diam., bears S.82*E., 84 lks. dist. Marked T 27 S R 2 W S 2 B T</p> <p>A fir, 32 ins. diam., bears S.75*W., 57 lks. dist. Marked T 27 S R 2 W S 3 B T (Orig. B.T.)</p> <p>A fir, 30 ins. diam., bears N.68*W., 55 lks. dist. Marked T 26 S R 2 W S 34 B T (Orig. B.T.)</p> <p>Land, mountainous Soil, stony clay loam, 3rd rate Timber, fir, cedar and madrona Undergrowth, hazel, vine-maple, arrowwood and fir</p>
	<p>I return to the cor. of secs. 19, 24, 25 and 30, on W. Bdy. of the Tp., established by Deputy Flint in 1855, which has evidently been renewed by a cedar post, 4 ins. sq., 12 ins. above ground, properly marked, witnessed as described by the surveyor general.</p> <p>Thence N.0*20*W. on a true line, on W bdy. of sec. 19 Over mountainous land, through dense timber and undergrowth Along E slope</p> <p>11.00 Ridge, bears NE and SW, descend NE slope</p> <p>26.35 Creek, 3 lks. wide, course NE, ascend SE slope</p> <p>30.00 Top of ascent, thence along E slope</p> <p>38.66 Intersect the $\frac{1}{4}$ sec. cor., reestablished by Deputy Gibb in 1910 and described by him as the original $\frac{1}{4}$ sec. cor. established by Deputy Flint in 1855, which is a hemlock post, 3 ins. sq. 12 ins. above ground, marked and witnessed as described by the surveyor general</p> <p>Thence N.0*10*W. continuing the measurement</p> <p>40.85 Ravine, course E, ascend SE slope</p> <p>46.00 Rocky point, slopes SE, ascend S slope</p>