

Resurvey of Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS	
4.00	Begin descent of steep NE slope
6.50	Descend bluff, 30 ft. high, continue descent over broken NE slope
42.90	Intersect the original $\frac{1}{4}$ sec. cor., established by Deputy McQuinn in 1883 and not reported found in any subsequent survey, which is a partly burned and decayed post, witnessed as described by the surveyor general, except for slight discrepancy in position of SW bearing tree. I now perpetuate this cor., as follows: at the exact cor. point Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked $\begin{array}{c} \frac{1}{4} \\ S23 S24 \\ 1916 \end{array}$ From which A fir, 48 ins. diam., bears N.50*E., 6 lks. dist. Marked $\frac{1}{4}$ S 24 B T (Orig. B.T.) A maple, 10 ins. diam., bears S.38*W., 30 lks. dist. Marked $\frac{1}{4}$ S 23 B T (Orig. B.T.) I destroy the corresponding cor. of the rejected revision survey and marks on bearing trees. Thence N.1*42'E., continuing the measurement
52.30	Descend bluff, 60 ft. high
55.50	Descend steep N slope to river
59.15	Left bank of North Umpqua River, course W
62.55	Right bank of river; ascend S slope river bank
63.10	Top of ascent; thence over river bottom
84.50	Leave river bottom and ascend
85.51	Intersect the cor. of secs. 13, 14, 23 and 24, established by Deputy McQuinn in 1883. The old post has been replaced at proper point by a basalt stone, 10x10x6 ins. above ground, firmly set, marked with 3 notches on S and 1