

Resurvey of Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS	<p>notch on E edge; witnessed as described by the surveyor general</p> <p>This cor. was also used as a cor. for the rejected revision survey.</p> <p>Land, mountainous and level</p> <p>Soil, to 63.00 chs., stony clay loam, 3rd rate; to 84.00 chs., deep sandy loam, 2nd rate; remainder, stony clay loam, 3rd rate</p> <p>Timber, fir, cedar, hemlock, sugar pine, maple and ash</p> <p>Undergrowth, vine maple, hazel and dogwood</p>
5.00	Trail, bears NW and SE
13.50	Top of ascent; thence along gentle S slope
35.00	Enter swamp
36.50	Leave swamp
40.01	<p>Intersect the $\frac{1}{4}$ sec. cor., established by Deputy McQuinn in 1883 and reestablished by U. S. Surveyor Collier in 1913, which is a basalt stone, 5x6x6 ins. above ground, firmly set, marked $\frac{1}{4}$ on N face, from which</p> <p style="padding-left: 40px;">A cedar, 18 ins. diam., bears N.55°E., 15 lks. dist. Marked $\frac{1}{4}$ S 13 B T (Orig. B.T.)</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S.47°30'W., 26 lks. dist. Marked $\frac{1}{4}$ S 24 B T</p> <p>Thence N.85°36'E., continuing the measurement</p>
41.75	Trail, bears NE and SW, descend E slope
45.45	Creek, 8 lks. wide, course S, gradually ascend SW slope
66.00	Low spur, slopes S, thence along broken S slope
69.75	Ravine, course S
78.55	Creek, 2 lks. wide, course S
79.85	Intersect the cor. of secs. 13 and 24, on E bdy. of the Tp. heretofore described in Book "J".