

Resurvey of Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS

70.75

Top of steep ascent; thence over nearly level bench

80.71

Intersect the original cor. established by Deputy McQuinn in 1883, as the cor. of secs. 22, 23, 26 and 27, which is a decayed post, witnessed as described by the surveyor general, except for slight discrepancies in position of bearing trees. The NW bearing tree has been cut down. I now perpetuate this cor., as follows: at the exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of secs. 22, 23, 26 and 27, with brass cap marked

T26S	R2W
S22	S23
S27	S26
1916	

Sec Page 4327
only 23 & 26
This corner changes to refer to secs 23 & 26 only
8-10-45
(BB)

from which

A fir, 18 ins. diam., bears N.43*E., 11 lks. dist.

Marked T 26 S R 2 W S 23 B T (Orig. B.T.)

A hemlock, 20 ins. diam., bears S.58*E., 55 lks.

dist. Marked T 26 S R 2 W S 26 B T (Orig. B. T.)

A cedar, 16 ins. diam., bears S.27*W., 45 lks. dist.

Marked T 26 S R 2 W S 27 B T (Orig. B.T.)

A hemlock, 10 ins. diam., bears N.23*W., 90 lks.

dist. Marked T 26 S R 2 W S 22 B T

From this cor. the cor. established by Deputy Gibb in 1909 as the closing cor. of secs. 26 and 27, on S bdy of sec. 23, which is a granite stone, 4x7x6 ins. above ground firmly set, marked and witnessed as described by the surveyor general, bears S.89*34'E., 9.26 chs. dist.

Also the cor. established by Deputy Gibb in 1909 as the closing cor. of secs. 22 and 27, on W bdy. of sec. 23, which is a granite stone, 5x10x8 ins. above ground, firmly set, marked and witnessed as described by the surveyor general, bears N.0*52'E., 14.96 chs. dist.