

Resurvey of Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS	Gradually descend N. slope
55.00	Creek, 8 lks. wide, course NW
67.75	Left bank of North Umpqua River, course W
71.85	Right bank of river; thence over level bottom land.
72.70	Trail, bears E and W.
78.20	Trail, bears NE and SW
83.00	Leave river bottom, bears E and W, ascend S slope
88.79	Intersect the cor. of secs. 14, 15, 22 and 23, established by Deputy McQuinn in 1883, which point is now marked by a basalt stone, 6x8x6 ins. above ground, firmly set, marked with 3 notches on S and 2 notches on E edge, witnessed as described by the surveyor general, except for slight discrepancies in the position of the bearing trees and that the NW tree is dead and the NE tree is dead and fallen. The SW tree, on account of the heavy bearing of the line bet. secs. 15 and 22, is not in the section to which it refers. I re-witness the cor. as follows: from the cor.  <div style="margin-left: 40px;">A fir, 12 ins. diam., bears N.51*30'E., 64 lks. dist. Marked T 26 S R 2 W S 14 B T</div> <div style="margin-left: 40px;">A fir, 24 ins. diam., bears S.46*E., 87 lks. dist. Marked T 26 S R 2 W S 23 B T (Orig. B.T.)</div> <div style="margin-left: 40px;">A laurel, 5 ins. diam., bears S.33*W., 25 lks. dist. Marked T 26 S R 2 W S 22 B T</div> <div style="margin-left: 40px;">A fir, 18 ins. diam., bears N.71*W., 74 lks. dist. Marked T 26 S R 2 W S 15 B T</div> <p>This cor. was also used as the cor. for the rejected revision survey</p> <p>Land, mountainous and level</p> <p>Soil, to 67.75 chs., stony clay loam, 3rd rate; to 83.00 chs., deep sandy loam, 2nd rate; remainder, stony clay loam, 3rd rate</p> <p>Timber, fir, cedar, hemlock and sugar pine</p>