

130
County Surveyor's Record, Douglas County, Oregon

Resurvey of Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS	
	Undergrowth, hemlock, fir, rhododendron, vine maple, hazel and huckleberry
	N.89*02'E., resurveying the line bet. secs. 14 and 23. Over rolling land, through dense timber and undergrowth, Descend SE slope
5.00	Foot of descent; thence level
11.20	Fence, bears N and S; enter old orchard
14.30	Fence, bears N and S; leave orchard
15.25	Trail, bears N and S
17.10	An old disused barn bears South, 60 lks. dist.
20.80	Susan Creek, 12 lks. wide, course S; gradually ascend SW slope
35.85	Trail, bears NW and SE
40.68	Intersect the $\frac{1}{4}$ sec. cor., established by Deputy McQuinn in 1883 and re-established by U. S. Surveyor Collier in 1913, which is a basalt stone, 5x8x8 ins. above ground firmly set, marked $\frac{1}{4}$ on N face, from which <div style="margin-left: 40px;">A fir, 18 ins. diam., bears S.59*E., 17 lks. dist. Marked $\frac{1}{4}$ S 23 B T (Orig. B.T.) A fir, 18 ins. diam., bears N.15*W., 15 lks. dist. Marked $\frac{1}{4}$ S 14 B T (Orig. B.T.)</div>
	Thence N.88*34'E., continuing the measurement
45.00	Low spur, slopes S; descend E slope
45.60	Trail, bears NE and SW
53.70	Creek, 3 lks. wide, course S; thence over level land
80.70	Leave level bottom land; ascend SW slope
81.21	Intersect the cor. of secs. 13, 14, 23 and 24, heretofore described Land, rolling and level Soil, to 5.00 chs., rocky clay loam, 3rd rate; to 25.00 chs., deep sandy loam, 2nd rate; to 54.00 chs. stony clay loam, 3rd rate; remainder, deep sandy loam, 2nd rate