

Resurvey of Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS

Timber, fir, cedar, sugar pine and laurel
Undergrowth, fir, vine maple, hazel and oak

I commence at the cor. of secs. 25, 26, 35 and 36, heretofore described.

Thence

West, on random line for distance only, on S bdy. of sec. 26.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.52 To intersection with W bdy. of sec. 26, 82.90 chs. S of cor. of secs. 23, 24, 25, and 26, heretofore described

At the point of intersection

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for SW cor. of sec. 26, with brass cap marked

T26S
R2W
S26
1916

from which

A cedar, 20 ins. diam., bears N.23°E., 37 lks. dist.

Marked T 26 S R 2 W S 26 B T

The cor. established by Deputy Gibb in 1909 as the cor. of secs. 26, 27, 34 and 35, which is a granite stone, 4x10x8 ins. above ground, firmly set, marked and witnessed as described by the surveyor general, bears N.23°53'E., 21.96 chs. dist.

I destroy the cor. set in the rejected revision survey as the cor. of secs. 26, 27, 34 and 35 and marks on bearing trees.

East, on a true line, on S bdy. of sec. 26

Over mountainous land, through dense timber and undergrowth

Along broken S slope

4.33 A fir, 30 ins. diam., marked with 2 notches on E and W sides

9.30 Creek, 1 lk. wide; course SE