

Resurvey of Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS	
	Over mountainous land, through dense timber and undergrowth
	Ascend SE slope
19.75	Ascend bluff, 20 ft. high
22.20	Trail, bears E and W
26.75	High ridge, divide bet. Little and North Umpqua Rivers bears E and W, descend NE slope
33.00	Descend steep rocky NE slope
34.75	Descend bluff, 20 ft. high
39.75	Foot of steep slope, descend gradually
41.45	(Midpoint) Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ cor. of sec. 26 only, with brass cap marked
	$\frac{1}{4}$ $\frac{1}{4}$ S 26 1916
	from which
	A fir, 6 ins. diam., bears N.28°E., 18 lks. dist. Marked $\frac{1}{4}$ S 26 B T
	A fir, 6 ins. diam., bears S.43°30'E., 64 lks. dist. Marked $\frac{1}{4}$ S 26 B T
	The cor. established by Deputy Gibb in 1909 as the $\frac{1}{4}$ sec. cor. on E bdy. of sec. 27, which is a granite stone, 5x12x5 ins. above ground, firmly set, marked and witness- ed as described by the surveyor general, except that no mound of stone is found, bears N.21°47'E., 18.67 chs. dist.
	The cor. reported established by Deputy Gibb in 1909 as the $\frac{1}{4}$ sec. cor. on W bdy. of sec. 26 is not found
	I destroy the cor. set in the rejected revision survey as the $\frac{1}{4}$ cor. of secs. 26 and 27 and marks on bearing trees
69.00	Descend over bluff, 20 ft. high, beginning descent of steep rocky N slope
74.75	Foot of steep descent, on bench of mountain
81.95	An old abandoned cabin bears West, 15 lks. dist.
82.90	Intersect the cor. of secs. 22, 23, 26 and 27 ? See Page 432)