

## Resurvey of Subdivisional Lines, T.26 S., R. 2 W.

CHAINS	
	<p>Land, mountainous</p> <p>Soil, stony clay loam and broken rock, 3rd and 4th rate</p> <p>Timber, fir, hemlock and cedar</p> <p>Undergrowth, hemlock, fir, snowbrush, chinquapin, arrow-wood and hazel</p>
	<p>I return to the cor. of secs. 2, 3, 34 and 35, on S bdy. of the Tp, heretofore described</p> <p>Thence</p> <p>North, bet. secs. 34 and 35</p> <p>Over mountainous land, through dense timber and undergrowth</p> <p>Gradually ascend SE slope</p>
17.85	Ravine, course SE
30.40	Spur, slopes E, descend NE slope
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{c} \frac{1}{4} \\ \text{S34} \mid \text{S35} \\ 1916 \end{array}$
	<p>from which</p> <p style="padding-left: 40px;">A hemlock, 18 ins. diam., bears S.55*30'E., 32 lks. dist. Marked <math>\frac{1}{4}</math> S 35 B T</p> <p style="padding-left: 40px;">A cedar, 24 ins. diam., bears N.80*W., 29 lks. dist. Marked <math>\frac{1}{4}</math> S 34 B T</p>
	<p>The cor. established by Deputy Gibb in 1909 as the <math>\frac{1}{4}</math> cor. of secs. 34 and 35, which is a granite stone, 4x9x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general, bears S.83*10'E., 2.06 chs. dist.</p>
	<p>I destroy the corresponding cor. set in the rejected re- vision survey and marks on bearing trees</p>
40.97	A fir, 40 ins. diam., marked with 2 notches on N and S sides
49.10	Creek, 2 lks. wide, course E, ascend S slope