

## County Surveyor's Record, Douglas County, Oregon

## Retracement and Resurvey of Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS		
	<p>above ground, marked and witnessed as described by the surveyor general</p> <p>The true course and distance of this line to the <math>\frac{1}{4}</math> sec. cor. is N.0°10'E., 39.65 chs.</p> <p>I destroy the corresponding cors. of the rejected revision survey and marks on bearing trees</p> <p>Thence, from the <math>\frac{1}{4}</math> sec. cor., I continue the retracement, N.0°02'W., counting distance from cor. of secs. 3, 4, 33 and 34</p>	
68.00	High ridge, divide bet. Little and North Umpqua Rivers,	
	bears E and W, trail on ridge, descend steep N slope	
79.55	Fall 25 lks. W of cor. of secs. 27, 28, 33 and 34, es-	
	tablished by Deputy Gibb in 1909, which is a granite	
	stone, 5x10x8 ins. above ground, firmly set, marked and	
	witnessed as described by the surveyor general, except	
	that the NE bearing tree is a hemlock instead of a fir,	
	and the SW bearing tree a cedar instead of a fir, as	
	described	
	The true course and distance of this line, from the $\frac{1}{4}$ sec.	
	cor. is N.0°20'E, 39.90 chs.	
	I destroy the cors. set in the rejected revision survey	
	as the cor. of secs. 27 and 34, and cor. of secs. 28 and	
	33 respectively, and marks on bearing trees.	
	Land, mountainous	
	Soil, stony clay loam, 3rd rate	
	Timber, fir, hemlock and cedar	
	Undergrowth, hazel, lilac, snowbrush and rhododendrons.	
	East, resurveying the line bet. secs. 27 and 34	
	Over mountainous land, through dense timber and undergrowth	
	Ascend steep NW slope	
3.20	Foot trail, bears N and S, on steep spur, sloping N	
23.50	Summit of divide bet. Little and North Umpqua Rivers, on	
	SW slope, ascend gradually along S slope of divide	