

Retracement and Resurvey of Subdivisional Lines, T. 26 S., R. 2 W.

CHAINS  
46.53

Intersect old S bdy. of sec. 17 and S bdy. of Tract No. 37,  
S.89°52'E., 6.50 chs. from cor. No. 4, hereinafter described.

At the point of intersection

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for closing cor. of secs. 20 and 21, with brass cap marked

T26SR2W  
S17  
-----  
S20 | S21  
T26S | R2W  
CC  
1916

from which

A fir, 40 ins. diam., bears S.46°E., 52 lks. dist.

Marked T 26 S R 2 W S 21 B T

A fir, 50 ins. diam., bears S.10°W., 16 lks. dist.

Marked T 26 S R 2 W S 20 B T

The cor. established by Deputy Gibb in 1909 as the closing cor. of secs. 20 and 21, which is a granite stone, 4x10x8 ins. above ground, firmly set, marked and witnessed as described by the surveyor general, bears N.29°E., 10 lks. dist.

Land, mountainous

Soil, rocky, 4th rate

Timber, fir, hemlock and cedar

Undergrowth, hazel, scrub oak and arrowwood

From the cor. of secs. 19, 20, 29 and 30, established by Deputy Gibb in 1909, which is a granite stone, firmly set, marked and witnessed as described by the surveyor general

Thence

North, retracing the line bet. secs. 19 and 20

Over mountainous land, through heavy timber and dense undergrowth.