

Survey of Tracts 37 and 38, T. 26 S., R. 2 W.

CHAINS

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for cor. No. 1 of Tract No. 37, with brass cap marked

S16	T26S
1	R2W
TR 37	S15
1918	

from which

A fir, 16 ins. diam., bears S.74*W., 50 lks. dist.

Marked 1
TR 37 B T

Thence

N.89*28'W., on N bdy. of Tract 37

Along gentle S slope, through heavy timber and dense undergrowth.

- 9.80 Top of small spur, slopes S; descend SW slope
- 17.70 Trail, bears NE and SW
- 25.30 Creek, 4 lks. wide, course SW; ascend gradual E slope
- 33.68 Creek, 2 lks. wide, course SE
- 54.50 Top of spur, slopes SW; descend W slope
- 70.50 Foot of descent; thence over level ground
- 76.20 North Umpqua trail, bears NW and SE
- 78.14 Intersect W bdy. of sec. 16 and temp. tract cor.

At the point of intersection

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for cor. No. 2 of Tract 37, with brass cap marked

T26S	S16
R2W	2
S17	TR 37
1918	

from which

A fir, 42 ins. diam., bears S.42*E., 90 lks. dist.

Marked 2 TR 37 B T

Land, mountainous

Soil, 1st 70.00 chs., stony clay loam, 3rd rate; remainder, sandy loam, 2nd rate

Timber, fir, hemlock and cedar

Undergrowth, chinquapin, rhododendron and hemlock